

Hose Types / Properties



Neptune

- Clear, food grade, PVC, material-handling hose.
- Smooth bore for better product movement.
- Suction and discharge of pellets and powders.
- Moderate abrasion resistance.
- Temperature range -10°C to +65°C (15°F to 150°F).
- 1.5"ID to 6"ID in 100' rolls or cut to length.



Neptune Static

- Clear, food-grade, PVC hose with internal static wire.
- Smooth bore for better product movement.
- Suction and discharge of pellets and powders.
- Moderate abrasion resistance.
- Temperature range -10°C to +65°C (15°F to 150°F).
- 1.5"ID to 6"ID in 100' rolls or cut to length



PU Vac

- Polyurethane hose reinforced with anti-shock helix.
- Smooth, clear, lightweight and flexible
- High abrasion resistance (5X superior to normal PVC).
- Suction and discharge of abrasive powders, fumes, shavings, chips, grain, cement and plastic pellets.
- Temperature range -20°C to +80°C (-4°F to 176°F).
- 1.5"ID to 6"ID in 100' rolls or cut to length.



Stainless & Galvanized Steel Hose

- Stripwound and interlocked metal hose ideal for pneumatic and dry-bulk conveying.
- Available with a smooth, abrasion-resistant metal liner for better product movement.
- Directional flow for optimum performance.
- Various end fittings such as flanges, stub ends and camlocks.
- 1.5"ID to 6"ID from 10' to 60' lengths.



Super Vac-U-Flex

- Grey, PVC hose for commercial or industrial vacuum cleaners and ventilating
- High-strength, fiber-reinforced cover with steel helix offers great flexibility.
- Temperature range -30°C to +65°C (-20°F to +150°F).
- 1.25"ID to 4"ID in 50' rolls (except 3" & 4" - 25') or cut to length.



Tan Bulkmaster

- Tan, weather-resistant, EPDM cover with steel helix.
- Smooth, abrasion-resistant, FDA-approved, rubber liner.
- Dry, abrasive materials such as corn, flour, sand, sugar, limestone powder and plastic pellets.
- Temperature range -32°C to +80°C (-25°F to +180°F).
- 2"ID to 6"ID in 100' rolls or cut to length.

Consult Factory For Other Types Of Hose Not Listed!